



# WOOD COATINGS AND WOOD STAINS



[www.paintachemindia.com](http://www.paintachemindia.com)

With more than 35 years of manufacturing experience in Coating and Thinners, PCI is well accepted as a reliable and trustworthy partner by customers. We serve multiple market segments and a variety of customers, from large scale manufacturers and exporters to small scale distributors and dealers.

PCI ensures direct, personal interaction with the customers, thereby eliminating the high cost involved in multi- layered distribution channels.

## PCI QUALITY POLICY

We delight customers with world class products and prompt service at competitive price.

We work with Pull approach by understanding the need of the market and bringing the desired products to fulfil the market requirements. Total Quality Management and the competent pricing policy at PCI are aimed to realize maximum leverage for its clients. Our product follows one specification of bringing customers the greatest satisfaction.

Our R&D division is always striving for better product for customers that add colours and value to them. With a commitment to excellence, we expect to achieve higher levels of customer satisfaction in the years to come.

### Quality Objectives:

- Customer driven, continuous improvement.
- Encouraging innovation & technology updation.
- Caring of requirements of end users.
- Compliance with documented quality systems.





## MELAMINE SEALER

Melamylne Sealer is used to prepare surface of wood before applying Melamine base top coat. It soaks into bare wood and gives a uniform & smooth surface for top coat. It is used to increase the life of Melamine top coat.

### Technical Data

Coverage: On smooth sanded wooden surface by spraying:  
8-10 sq.mtr/ltr/coat

Drying Time: Surface Dry time  $\approx$  10 minutes, Tack free time  $\approx$  1 hrs

Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.



## MELAMINE CLEAR

PCI Melamylne Top Coat is an acid curing solvent based 2 pack wood finishes. It is specifically formulated as a protective & decorative clear coating of wood. It protects the Interior wood for many years. It has got excellent resistance to staining from oils, foods & hot beverages. It is available in Glossy, Satin & Matt finish.

### Technical Data

Coverage: On smooth sanded wooden surface by spraying:  
8-10 sq.mtr/ltr/coat

Drying Time: Surface Dry time  $\approx$  10 minutes, Tack free time  $\approx$  1 hrs

Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.



## SANDING SEALER

Sanding sealer is a fast, economical way to seal wood and prepare the surface for the application of a clear topcoat finish. It soaks into bare wood quickly to completely seal the wood grain, which is critical for creating a smooth, even topcoat.

### Technical Data

Solid Contents:	Approximate 40 %
Drying Time:	5-7 minutes
THINNER:	PCI T-022, T-011, T-020
Coverage:	8 to 10 sq.mtr/ltr

(It depends on method of application and coat thickness)



## POLYURETHANE CLEAR

PU (Interior & Exterior) is a global quality product, which is specially formulated for the protection of your wood for years and gives a royal finish to your furniture. PCI polyurethane varnish is clear polyurethane based varnish for all types of furniture and wood. It provides a glossy durable film which is highly resistant to water, alcohol and usual household chemicals. It gives a decorative finish to the surface with protection. It is available in Glossy, Satin & Matt finish.

### Technical Data

Coverage:	On smooth sanded wooden surface by spraying: 8-10 sq.mtr/ltr/coat
Drying Time:	Surface Dry time $\approx$ 10 minutes, Tack free time $\approx$ 1 hrs

Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.



## T.T. CLEAR

A sport clear is nitrocellulose based high quality economic clear lacquer. It is recommended for interior wooden furniture. Sports Clear is available in both glossy and matte finish.

### Technical Data

Method of Application:	Spray
Recommended Thinner:	PCI T-022
Weight per Ltr.:	0.985 approx.
Coverage:	8-10 sq.mt/Ltr/coat



## POLYURETHANE SEALER

P.U. Sealer is used to prepare surface of wood before applying P.U base top coat. It soaks into bare wood and gives a uniform & smooth surface for top coat. It is used to increase the life of P.U top coat.

### Technical Data

Coverage:	On smooth sanded wooden surface by spraying: 8-10 sq.mtr/ltr/coat
Drying Time:	Surface Dry time ≈ 10 minutes, Tack free time ≈ 1 hrs.

Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness.






**TEAK**




**ORANGE**



**WALNUT**



**DARK BROWN MAHAGONY**




**ROSEWOOD**




**RED BROWN**




**YELLOW OAK**



**DARK BROWN OAK**




**DARK ANTIQUE PINE**



**BLACK**



**LIGHT GOLDEN OAK**



**DARK RED MAHOGANY**

We have variety of products in three different divisions to fulfill market requirements alongside Automotive Paints.

## Thinner

All kinds of thinner including Acrylic, Epoxy, Enamel, Polyurethane, nitro-cellulose and stoving etc. containing 100% genuine chemicals in formulation with no distilled or poor quality chemicals.

## Industrial Coating

We provide various paints for industries like Protective coatings (Epoxy based), Heat-resistant paint, Glass coats, Fluorescent paints, Thermoplastic acrylic (Food Grade), Thermosetting acrylic, Strippable lacquers, Corrosion resistant paints, Floor-coatings, Casting Lacquers, Wood bleaching Agents, Dyestuff solutions etc.

## PAINTA CHEM [INDIA]

AN ISO 9001:2008 CERTIFIED COMPANY

Automotive Paints | Thinners | Industrial Coating

4th Milestone Meerut Road, Hapur-245101 (U.P.)

Phone : +91-99970 82288, +91-98370 42829

Email : [contact@paintachemindia.com](mailto:contact@paintachemindia.com)